

EXHIBIT A

8

Reissue of U. S. Patent No. 5,630,363

CLAIMS

Note: Bracketed material in the following claims has been deleted from U. S. Patent 5,630,363 as issued; underlined materials, including new claims 42-87 has been added.

1. Apparatus for a combined lithographic/flexographic printing process comprising:

a substrate;

a plurality of successive printing stations for printing color images on the substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a liquid vehicle image on said substrate with a slurry containing an encapsulated essence using the flexographic process;

at least one of said successive printing stations being a lithographic printing station; and

an overcoating applied over the liquid vehicle image on the printed substrate at at least one of said successive lithographic printing stations using the lithographic process in said continuous in-line process.

2. Apparatus as in claim 1 wherein said overcoating is an aqueous overcoating.

3. Apparatus as in claim 1 wherein said overcoating is an ultraviolet ink overcoating.

0915796-05009

09315796-042094

4. Apparatus as in claim 1 wherein:

said substrate is a paper sheet; and

said apparatus includes a sheet feeder.

5. Apparatus as in claim 1 wherein:

said substrate is a web; and

said apparatus includes a web feeder.

6. Apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station printing an aqueous-based vehicle image using the flexographic process to form a metallic coating;

a suspended metallic material being included in said aqueous-based vehicle image; and

at least one of the successive printing stations comprising an offset lithographic printing station printing a color image over the aqueous-based vehicle image using the offset lithographic process in said continuous in-line process.

7. Apparatus as in claim 6 wherein said suspended material includes uniform-sized metal particles to form said metallic coating.

8. Apparatus as in claim 6 wherein said suspended material includes nonuniform-sized metal particles to form said metallic coating.

9. Apparatus as in claim 6 further including: said flexographic printing station including a plate cylinder having a flexographic plate thereon, a blanket cylinder, and an impression cylinder;

a flexographic plate image transferred from said plate cylinder to said blanket cylinder, said image being formed of said metallic coating, said blanket cylinder transferring said metallic coating to said impression cylinder for printing said flexographic plate image on said substrate; and

an anilox roller associated with said flexographic plate for supplying said aqueous-based vehicle containing said suspended metallic material to said flexographic plate.

10. Apparatus for creating a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a first color image using the flexographic process; and

at least one of the successive printing stations comprising an offset lithographic printing station for printing a second color image over the first color image using the offset lithographic process in said continuous in-line process.

11. Apparatus as in claim 10 further including:

said flexographic printing station including a plate cylinder, a blanket cylinder, and an impression cylinder;

a flexographic plate on said plate cylinder;

an anilox roller associated with said flexographic plate for supplying a first color to said flexographic plate to form said first color image; and

said blanket cylinder receiving said first color image from said plate cylinder and transferring said first color image to said impression cylinder for printing on said substrate.

12. (Amended) Apparatus for creating a combined lithographic/flexographic printing process comprising:

a substrate;

a plurality of successive printing stations for printing color images on the substrate in a continuous in-line process;

at least two successive ones of said printing stations being flexography stations and comprising:

(1) a supply of liquid coating;

(2) a plate cylinder associated with a blanket cylinder, said plate cylinder having a flexographic plate thereon;

(3) an anilox roller associated with said liquid supply coating and said plate cylinder for delivering said liquid coating to said flexographic plate to form an image for transfer to said blanket cylinder;

(4) an impression cylinder holding said substrate for receiving said liquid coating image transferred from said blanket cylinder and printing said image on said substrate[,];

said at least two flexography stations printing the same liquid coating image in sequence and in superimposed relationship; and

at least one offset lithographic printing station [for] receiving said substrate and printing over said liquid coating image.

13. Apparatus as in claim 12 wherein said liquid coating image printed on said substrate is a white color ink.

6033-96767

14. Apparatus as in claim 12 further including an air dryer associated with each of said impression cylinders on said flexography stations, said air dryer having sufficient air velocity for drying said liquid coating before the substrate is transferred to the successive printing station in said continuous in-line process.

15. Apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

a blanket cylinder at at least a first one of said flexographic printing stations;

flexographic ink-providing means at said at least first one of said flexographic printing stations for applying a flexographic ink to said blanket cylinder to form an image;

a substrate for receiving said flexographic ink image transferred from said blanket cylinder; and

at least one subsequent lithographic printing station in said in-line process for receiving said image printed substrate and printing an additional colored ink image on said substrate on top of said flexographic ink image using offset lithography.

16. Apparatus as in claim 15 further comprising:

a plate cylinder at said at least first one of said flexographic stations;

a flexographic plate on said plate cylinder for receiving and transferring said flexographic ink to said blanket cylinder; and

said flexographic ink-providing means including a flexographic ink supply and an anilox roller associated with said flexographic ink supply for transferring said flexographic ink to said flexographic plate.

17. Apparatus for a combined lithographic/flexographic printing process for printing a multicolored image comprising:

a plurality of successive printing stations for printing color on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

at least one of said flexographic printing stations having:

(1) a plate cylinder and a blanket cylinder, said plate cylinder including a flexographic plate having an image thereon for transferring a flexographic color ink image to said blanket cylinder;

(2) an etched anilox roller for applying a flexographic color ink to said flexographic plate on said plate cylinder;

(3) an impression cylinder in ink-transfer relationship with said blanket cylinder for transferring said flexographic color ink image from said blanket cylinder to said substrate; and

at least one of said succeeding printing stations being a lithographic printing station using offset lithography for printing additional colored ink images on top of said flexographic ink image.

18. Apparatus as in claim 17 wherein said additional colored ink images are formed with lithographic inks.

19. (Amended) Apparatus as in claim 17 wherein at least one of the said colored ink images [are] is formed with a waterless [inks] ink.

20. (Amended) Apparatus as in claim 17 further including an air dryer adjacent to said impression cylinder for drying the colored flexographic ink image transferred to said substrate before said additional colored ink images are printed thereon.

6502270-9525T660

transferring said printed substrate to at least one subsequent printing station in said continuous in-line process; and

printing colored ink images [on top of] over said flexographic ink image at at least one of said subsequent lithographic printing stations with an offset lithographic process.

30. A method as in claim 29 further comprising the step of drying said flexographic ink image on said substrate with an air dryer prior to printing said colored ink images thereon.

31. A method as in claim 29 further including the step of printing a coating on top of said colored ink images at one of said plurality of subsequent printing stations.

32. A method as in claim 29 wherein said colored inks forming said colored ink images are waterless.

33. A method as in claim 29 wherein said colored inks forming said colored ink images are in a solvent-based liquid vehicle.

34. (Amended) A method as in claim 29 further including the steps of:

printing a slurry on said substrate at any of said printing stations in said continuous in-line process;

using an encapsulated essence in said slurry; and

printing an overcoating [over] on top of said slurry at a subsequent printing station in said in-line process to protect said essence.

35. A method as in claim 34 further including the step of printing an aqueous-based coating over said slurry.

36. A method as in claim 34 further including the step of printing an ultraviolet coating over said slurry.

560230-96257267

37. A method of combining offset lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a substrate;

applying a flexographic ink to a blanket cylinder in a pattern with a coating head at a first flexographic printing station;

transferring said pattern of flexographic ink from said blanket cylinder to the substrate; and

printing a waterless ink pattern over said flexographic ink pattern on said substrate at at least one subsequent offset lithographic printing station in said continuous in-line process.

38. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

printing an aqueous-based vehicle image having suspended particles therein on a substrate at a first flexographic printing station;

transferring said image printed substrate to at least one additional printing station in said continuous in-line process; and

printing additional colored ink images on said printed substrate over said aqueous-based vehicle image in an offset lithographic process at said at least one additional printing station in said in-line process.

39. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

(1) providing a plurality of successive printing stations for printing liquid vehicle images on a substrate in said in-line continuous process;

(2) utilizing an anilox roller to transfer a liquid ink as said liquid vehicle to a flexographic plate image at at least one of said printing stations;

(3) printing said liquid ink from said flexographic plate image to a substrate;

(4) transferring said printed substrate with said liquid ink image to a subsequent printing station in said in-line printing process;

(5) repeating steps (2)-(4) at subsequent printing stations in said in-line process to achieve a desired opacity ink image on said substrate; and

(6) printing an ink pattern over said flexographic ink image using an offset lithographic process.

40. A method as in claim 39 further including the step of additionally printing colored ink images over said liquid ink image on said substrate at subsequent ones of said printing stations in said in-line process.

41. A method as in claim 40 wherein said liquid ink is an opaque white color.

42. The apparatus of any of claims 1, 6, 10, 12, 15 and 17, wherein the substrate is printed on both sides in one pass during the continuous in-line process.

43. The method of any of claims 29, 37, 38 or 39 wherein the substrate is printed on both sides in one pass during the continuous in-line process.

44. Apparatus for a combined lithographic/flexographic printing process comprising:

a substrate;

a plurality of successive printing stations for depositing a series of images on one side of a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a liquid vehicle image on said substrate using a flexographic process; and

at least one of said successive printing stations being a lithographic printing station;

whereby said substrate is printed on top of or on the opposite side of that previously printed at at least one of said successive lithographic printing stations using the lithographic process in said continuous in-line process.

45. Apparatus as in claim 44 wherein at least one of said images at the flexographic station is a coating material.

46. Apparatus as in claim 44 wherein at least one of said images at one of the lithographic stations is an ink.

47. Apparatus as in claim 44 wherein:

said substrate is a paper sheet; and

said apparatus includes a sheet feeder.

48. Apparatus as in claim 44 wherein:

said substrate is a web; and

said apparatus includes a web feeder.

49. An apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station printing an aqueous-based vehicle on one side of the substrate using the flexographic process to form a metallic coating image;

(1) a supply of liquid coating;

(2) a plate cylinder associated with a blanket cylinder, said plate cylinder having a flexographic plate thereon;

(3) an anilox roller associated with said liquid supply coating and said plate cylinder for delivering said liquid coating to said flexographic plate to form an image for transfer to said blanket cylinder;

(4) an impression cylinder for receiving said liquid coating image transferred from said blanket cylinder and printing said image on one side of said substrate; and

at least one offset lithographic printing station for receiving said substrate and printing on top of or on the opposite side to that previously printed.

56. Apparatus as in claim 55 wherein said liquid coating image printed on said substrate is a white color ink.

57. Apparatus as in claim 56 further including an air dryer associated with each impression cylinder on each flexographic station, said air dryer having sufficient air velocity for drying said liquid coating before the substrate is transferred to the successive printing station in said continuous in-line process.

58. Apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process, said printing stations including both lithographic and at least two flexographic printing stations;

a blanket cylinder at at least a first one of said flexographic printing stations;

flexographic ink-providing means at the other of said flexographic printing stations for applying a flexographic ink to said blanket cylinder to form an image on one side of a substrate;

a substrate for receiving said flexographic ink image transferred from said blanket cylinder; and

at least one subsequent lithographic printing station in said in-line process for receiving said image printed substrate and printing an additional colored ink image on said substrate on top of said flexographic ink image or the opposite side to that previously printed using offset lithography.

59. Apparatus as in claim 58 further comprising:

a plate cylinder at said at least first one of said flexographic stations;

a flexographic plate on said plate cylinder for receiving and transferring said flexographic ink to said blanket cylinder; and

said flexographic ink-providing means including a flexographic ink supply and an anilox roller associated with said flexographic ink supply for transferring said flexographic ink to said flexographic plate.

60. Apparatus for a combined lithographic/flexographic printing process for printing a multicolored image comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

at least one of said flexographic printing stations having:

(1) a plate cylinder and a blanket cylinder, said plate cylinder including a flexographic plate having an image thereon for transferring a flexographic color ink image to said blanket cylinder;

(2) an etched anilox roller for applying a flexographic color ink to said flexographic plate on said plate cylinder;

(3) an impression cylinder in ink-transfer relationship with said blanket cylinder for transferring said flexographic color ink image from said blanket cylinder to one side of said substrate; and

at least one of said succeeding printing stations being a lithographic printing station using offset lithography for printing additional colored ink images on top of said flexographic ink image or on the opposite side to that that previously printed.

61. Apparatus as in claim 60 wherein said additional colored ink images are formed with lithographic inks.

62. Apparatus as in claim 60 wherein at least one of said colored ink images is formed with a waterless ink.

63. Apparatus as in claim 60 further including an air dryer adjacent to said impression cylinder for drying the colored flexographic ink image transferred to said substrate before said additional colored ink images are printed thereon.

64. Apparatus as in claim 60 further including halftone printing plates for printing said colored ink images.

65. Apparatus as in claim 60 wherein said colored flexographic ink image and said lithographic colored ink images are printed as solid colors and/or with halftone printing plates in sequence and in registry in said successive printing stations to produce said multicolored image on said substrate.

66. Apparatus as in claim 60 wherein said printing apparatus includes a sheet-fed press.

67. Apparatus as in claim 60 wherein at least one of said flexographic printing stations prints said flexographic ink image with liquid vehicle slurry containing an encapsulated essence.

68. Apparatus as in claim 60 wherein at least one of said printing stations prints said flexographic ink image with a water-based liquid vehicle containing suspended particles.

69. Apparatus as in claim 68 wherein said suspended particles are uniform in size.

70. Apparatus as in claim 68 wherein said suspended particles are nonuniform in size.

71. Apparatus as in claim 68 wherein said suspended particles are metallic particles.

72. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a plurality of successive lithographic/flexographic printing stations for depositing a series of images on a substrate;

printing an image as one of said thin controlled layers on one side of said substrate at at least one of said flexographic stations;

transferring said printed substrate to at least one subsequent printing station in said continuous in-line process; and

printing an image on the reverse side of said substrate having said flexographic ink image, at at least one of said other subsequent lithographic printing stations with an offset lithographic process in the continuous in-line process.

73. A method as in claim 72 further comprising the step of drying said flexographic ink image on said substrate with an air dryer prior to printing said colored ink images thereon.

74. A method as in claim 72 further including the step of printing a coating on top of said colored ink images at one of said plurality of subsequent printing stations.

75. A method as in claim 72 wherein said colored inks forming said colored ink images are waterless.

76. A method as in claim 72 wherein said colored inks forming said colored ink images are in a solvent-based liquid vehicle.

77. A method as in claim 72 further including the steps of:

printing a slurry on one side of said substrate at any of said printing stations in said continuous in-line process;

using an encapsulated essence in said slurry; and

printing an ink on the reverse side of said substrate at a subsequent printing station in said in-line process.

78. A method as in claim 77 further including the step of printing an aqueous-based coating over said slurry.

79. A method as in claim 77 further including the step of printing an ultraviolet coating over said slurry.

80. A method of combining offset lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a substrate;

applying an ink or coating to a blanket cylinder in a pattern with a coating head at a flexographic printing station;

transferring said pattern of ink or coating from said blanket cylinder to one side of the substrate; and

printing a waterless ink pattern on the reverse side of said substrate at at least one subsequent offset lithographic printing station in said continuous in-line process.

669250-3625260

81. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

printing an aqueous-based vehicle having suspended particles therein on one side of a substrate at a flexographic printing station to form an image;

transferring said image printed substrate to at least one additional printing station in said continuous in-line process; and

printing additional images on the reverse side of said printed substrate in an offset lithographic process at said at least one additional printing station in said in-line process.

82. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

(1) providing a plurality of successive printing stations for depositing a series of images on a substrate in said in-line continuous process;

(2) utilizing an anilox roller to transfer a liquid ink as one of said thin controlled layers to a flexographic plate image at at least one of said printing stations;

(3) printing said liquid ink from said flexographic plate image to one side of a substrate;

(4) transferring said printed substrate with said liquid ink image to a subsequent printing station in said in-line printing process;

(5) repeating steps (2)-(4) at subsequent printing stations in said in-line process to achieve a desired opacity ink image on the one side of said substrate; and

(6) printing an ink pattern on the reverse side of said substrate using an offset lithographic process.

650760-3457E60

83. A method as in claim 82 further including the step of additionally printing ink images over said liquid ink image on said substrate at subsequent ones of said printing stations in said in-line process.

84. A method as in claim 83 wherein said liquid ink is an opaque white color.

85. A method of combining offset lithography and flexography using a plurality of successive printing stations in a continuous in-line process, at least one of said stations comprising a flexographic printing station for printing an image on said substrate using a flexographic process:

(1) printing an image at one or more of said printing stations on a substrate using an offset lithographic process;

(2) transferring said image printed substrate to an additional and flexographic printing station and printing at said flexographic and additional printing station a coating on all or part of said image on said substrate;

(3) transferring said substrate to one or more additional printing stations for printing the reverse side of the said substrate; and

(4) printing an image on said reverse side of said substrate at one of such one or more printing stations using an offset lithographic process in the continuous in-line process.

86. Apparatus for a combined offset lithographic and flexographic printing process comprising:

(1) a substrate;

(2) a plurality of successive printing stations for depositing a series of images selected from a group consisting of lithographic and flexographic inks, coatings and slurries on one or both sides of a substrate in a continuous in-line process;

(3) at least one of said stations comprising a flexographic printing station for printing an image on said substrate using a flexographic process;

(4) at least one of said successive printing stations being an offset lithographic printing station whereby said offset lithographic printing station is used to deposit one of said lithographic materials on either side of the said substrate in the continuous in-line process;

87. Apparatus for a combined offset lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing images on a substrate in a continuous in-line process, said printing stations including both offset lithographic and flexographic printing stations for depositing lithographic inks, and one or more flexographic inks, coatings and slurries on said substrate, whereby said lithographic inks, and one or more flexographic inks, coatings and slurries may be printed successively on one or both sides of said substrate in the continuous in-line process.

60250-064760